

High performance for Mold & Die

# Deep hole drilling tool Type 01 combined with Cutting inserts with chip breaker SP91

Ø 12.00 - 43.99 mm



- → High performance deep hole drilling tool with a modern, user-friendly design.
- → Cutting inserts for high productivity and wide range of application.
- → Together the perfect combination for machining mold base steel

### Advantages:

- → Very high operational efficiency combined with optimum cutting capacity.
- → Easy exchange of indexable inserts and guide pads. No need to adjust setting.
- → Model with extended guide pads is also suitable for **crosshole drilling**.



### Application

- For machining centres with internal coolant up to 40 x D.
- With the rotating coolant connector by botek for large tool diametres and flow rates up to 250 l/min.
- For gundrilling machines up to 2500 mm tool length.
- From dia. 12.00 to 17.99 mm feed rates of up to fz 0.12 mm/rev. can be realized.
- From dia. 18.00 mm onwards values up to fz 0.18 mm/rev. are possible.















## **Advantages:**

- → Higher feedrate and higher cutting speed compared to chip breakers SP1 and SP2
- → Up to 400% higher productivity and more compared to conventional/brazed gundrills
- → **Higher lifetime per insert** together with improved process reliability
- → Positive chip breaker for good chip control also with long chipping steels
- → Application for material groups ISO P and ISO M and special Mold Base Steel
- → Available in standard grades K30BX (Ø 12.00 17.99 mm) and P25BX (Ø 18.00 - 43.99 mm)

### Service:

- → Process design
- → Customer testing in our trial department
- → Stock program

  Immediately available
  Fast and simple processing
- → Please see our new homepage, www.botek.de/de/online-shop

# More information can be found at www.botek.de

botek

Präzisionsbohrtechnik GmbH

Längenfeldstraße 4 ⋅ 72585 Riederich ⋅ Germany **P** +49 7123 3808-0 **www**.botek.de