Deep hole drilling in new dimensions Deep hole drilling tool Type 01 NEW: from Ø 11.00 mm

- → For use on BAZ and deep hole drilling machine.
- → Stock program.
- ightarrow High performance deep hole drilling tool with a modern, user-friendly design.
- → Cutting inserts for high productivity and universal use.

Advantages:

- New, high performance deep hole drilling tools with a modern, user-friendly design.
- Very high operational efficiency combined with optimum cutting capacity.
- Very good drilling quality.
- New high performance cutting inserts 225S-91 for high productivity and process reliability.
- No regrinding needed.
- Cutting inserts and guide pads can be exchanged on the machine, with the simplest handling, without re-adjustment of the setting within \pm 0.01mm.

Application area:

- Ø 11.00 43.99 mm complete range, NEW: Ø 11.00 - 11.99 mm.
- For deep hole drilling machines at tool lengths up to 2,500 mm.
- For process-safe deep hole drilling on machining centres we recommend our rotating coolant connector
- Version with extended guide pads (Type 01-011) also suitable for crosshole drilling.

Please inquire with us. For more information visit www.botek.de



botek Präzisionsbohrtechnik GmbH · Längenfeldstraße 4 · 72585 Riederich · Germany **P** +49 7123 3808-0 · **E-Mail** Info@botek.de · **www**.botek.de

Application examples:

Material Tensile strength (N/mm²) Drill-Ø (mm):	20MnCr5 1.7147 850	X5CrNi18-10 1.4301 620	40CrMnNiMo8-6-4 1.2738	X37CrMoV5-1 1.2343
-				
-	850	620		
Drill @ (mm):		020	43HRC	1050
(חוווט).	11.00	11.00	11.00	11.00
Cutting insert:	2255-91	2255-91	2255-91	2255-91
Vc (m/min):	90	80	75	80
Vf (mm/min):	230	200	186	200
Coolant pressure (bar):	70	85	70	70

Spare parts:

	Drilling range				
Drill-Ø	Type 01-001 Standard version with 2 guide pads	Type 01-011 Standard version with 4 guide pads			
Ø (mm)					
11.00 - 11.49	01-111X-001	01-111X-011			
11.50 - 11.99	01-112X-001	01-112X-011			

Ordering example: 01-1113-001-11,00-1000-ZH16-31

<u>01 - 111 3 - 001 - 11,00 - 1000 - ZH16-31</u>

Туре	Drilling range Ø 11.00-11.49 mm	Length group 3	Standard version with two guide pads	Drill-Ø 11.00 mm	Over all length 1,000 mm	Driver ZH16-31

Service:

- → Process layout
- → Customer trials in our research and development department
- → Stock program
- → Download and ordering information available on our website www.botek.de/de/online-shop

Download and ordering information available on our website

www.botek.de

250 000 322/09-2022

→ Technical Hotline: +49 7123 3808-200